

**TOR
GROUP****15M GENERAL SERVICE BOAT**

GENERAL INFO	
Basic Function	General Service Boat for mooring & transfer operations at port
Design	Macduff Ship Design Ltd.

MAIN PARTICULARS	
Length Over All (LOA)	15.0m
Breadth (B)	4.8m
Depth (D)	2.15m
Draught (Max)	1.20m
Speed	11 Knots

CLASSIFICATION	
Class Society	Bureau Veritas (BV)
Class Notation	BV-I ⚡ HULL • Mach, Lunch

TANK CAPACITIES	
Fuel	2,044 Litres
Fresh Water	294 Litres
Sewage	100 Litres
Lub oil	154 Litres

FIRE & SAFETY	
Safety Equipment	1 x 8-man inflatable Life raft
	Fire Detection and Alarm System
	Adequate Foam & Dry Powder Extinguishers

ACCOMMODATION & NAVIGATION	
Accommodation	1 x WC below deck, 5 Crew Seats in wheelhouse.
Search Light	1 x 500W 24V, 360°, Manual Control
Air Condition	12000 BTU split AC for bridge
Navigation & Communication Equipment	1 x Radar 1 x GPS 1 x AIS 1 x Wind Sensor 2 x VHF 1 x Magnetic Compass

DECK MACHINERY	
Windlass	Max pull 1250 kg.
Anchor	50 kg. HHP YP power type anchor
Chains	12.5 mm Grade Q2 stud link

MACHINERY	
Main Engine	2 x 287 kW @ 1800 rpm
Fire & Bilge Pump	2 x 30 m³/h @ 2.5 bar
Submersible Bilge Pump	5 m³/h @ 1 bar
FW Pressure Set	17lt/min 24V
Black Water Pump	7 m³/h @ 1.5 bar
Emergency Fire Pump	Moto pump 420lt/min-2bar max with 7lt fuel tank



TOR
GROUP

15M GENERAL SERVICE BOAT

